

COPPER FLAT BAR
DETAILED SPECIFICATION OF PRODUCT RANGE AND THEORETICAL WEIGHT
L- 3300 mm and 4000 mm

Width in mm	Thickness in mm	Weight kg/m
20	3.00	0.53
	4.00	0.71
	5.00	0.89
	6.00	1.07
	10.00	1.78
25	3.00	0.67
	4.00	0.89
	5.00	1.11
	6.00	1.34
	10.00	2.23
30	3.00	0.80
	4.00	1.07
	5.00	1.34
	6.00	1.60
	10.00	2.67
40	3.00	1.07
	4.00	1.42
	5.00	1.78
	6.00	2.14
	10.00	3.56
50	3.00	1.34
	4.00	1.78
	5.00	2.23
	6.00	2.67
	10.00	4.45
60	3.00	1.60
	4.00	2.14
	5.00	2.67
	6.00	3.20
	10.00	5.34
80	3.00	2.14
	4.00	2.85
	5.00	3.56
	6.00	4.27
	10.00	7.12
100	3.00	2.67
	4.00	3.56
	5.00	4.45
	6.00	5.34
	10.00	8.90



The weights specified in these tables are theoretical and established based on a unique formula for calculating the weight of drawn copper products (product tolerances in accordance with the EN standard).